

# CLICK WOOD & STONE

## RIGICORE 5.5

CONSTRUCTION / CONSTRUCTION / COSTRUZIONE / CONSTRUCTIE

TOTAL THICKNESS / EPAISSEUR TOTALE / SPESSORE / TOTALE DIKTE

WEAR LAYER / COUCHE D'USURE / STRATO D'USURA / SLIJTLAG

UTILIZATION CLASS / CLASSE D'USAGE / CLASSE D'UTILIZZO / GEBRUIKERSKLASSE

COATING / PROTECTION / RIVESTIMENTO / BESCHERMING

EMBOSSING / STRUCTURE / STRUTTURA / STRUCTUUR

BEVELLED / BISEAUTÉ / BISELLATURA / V-GROEF

PLANK SIZE / DIMENSIONS DE LA LAME / DIMENSIONI / AFMETING PER PANEEL

CARTON PACKING / EMBALLAGES EN CARTON / SCATOLE / KARTONNEN VERPAKKING

PALLET PACKING / BÔTES PAR PALETTE / NR SCATOLE À PALETTE / DOZEN PER PALLET

NET- GROSS WEIGHT PER PALLET / POIDS NET-BRUT PAR PALETTE / PESO NETTO - LORDO À PALETTE / GEWICHT NETTO - BRUTO PER PALLET

CASTOR CHAIR RESISTANCE / ESSAI DE LA CHAISE À ROULETTES / PROVA CON POLTRONA A ROTELLE / ROLWEERSTAND BUREAUSTOEL EN ISO 4918 - EN 425

EFFECT OF FURNITURE LEG / EFFECT DE PIED DE MEUBLE / EFFETTO DL GAMBE MOBILI / EFFECT VAN MEUBILAIR POTEN EN424

ELECTROSTATIC PERFORMANCE / POTENTIEL DE CHARGE ELECTROSTATIQUE / POTENZIALE DL CARICA ELETTRISTATICA / ELECTROSTATISCHE EIGENSCHAPPEN EN 1815

SLIP RESISTANCE / ANTIDÉPARANT / RESISTENZA ALLO SCIOLVAMENTO / SLIPWEERSTAND DIN 51130

WEAR RESISTANCE / RÉSISTANCE D'USURE / RESISTANCE ALL'USURA / SLIJTVASTHEID EN 660 -2

RESIDUAL INDENTATION / POINÇONNEMENT RÉMANENT / SENSIBILITÀ DL IMPRESSIONE / INDRUKGEVOELIGHEID EN ISO 24343-1

DIMENSIONAL STABILITY / STABILITÉ DIMENSIONNELLE / STABILITÀ DIMENSIONALE / DIMENSIONALE STABILITEIT EN434

FIRE RATING / CLASSIFICATION AU FEU / CLASSIFICAZIONE AL FUOCO / BRANDKLASSE EN ISO 9239-1

FORMALDEHYDE EMISSION / EMISSION DE FORMALDEHYDE / SENSIBILITÀ DL IMPRESSIONE / INDRUKGEVOELIGHEID EN717-1

WARRANTY FOR DOMESTIC USE / PÉRIODE DE GARANTIE USAGE DOMESTIQUE / GARANZIA PER USO DOMESTICO / GARANTIEPERIODE HUISHOUDELIJK GEBRUIK

WARRANTY FOR COMMERCIAL USE / PÉRIODE DE GARANTIE USAGE COMMERCIAL / GARANZIA PER USO COMMERCIALE / GARANTIEPERIODE COMMERCIEEL GEBRUIK

### WIDE PLANK\* RIGICORE 5,5

4.0 MM RIGICORE + 1.5 MM IXPE



5.5 MM



0.55 MM



CLASSE 33  
CLASSE 42

PU

NATURAL + TRU-WOOD

YES

220 X 1219 MM

2.146 SQM / 8 PLANKS

44 PACKS / PALLET

820 KG / 860 KG



PASS



PASS



AVERAGE - 2.0 kV

R9/R10 DEPENDING ON EMBOSSING



GROUP T



PASS



PASS



BFL-S1



CLASS E1

25 YEAR

10 YEAR

\* GLUEDOWN 2.5 TECHNICAL SPECIFICATIONS ARE AVAILABLE ON DEMAND

**10** YEAR  
GUARANTEE  
COMMERCIAL

**25** YEAR  
GUARANTEE  
DOMESTIC

**VIRGIN**  
100%-PROLARE TRVL

**A+**  
A+ A B C

100%  
FIBRALLET  
100%

**floor**  
score

**CE**  
EN 14041



WWW.CONTESSE-FLOORS.COM